



170.298 PORTABLE PA SYSTEM – 75w + 75w RMS

The system consists of a 4 channel stereo mixer amplifier and a pair of 2-way speaker enclosures which can be fixed together to form a portable / mobile unit with integral wheels and retractable handle. Ideal for aerobic instructors, presentations, seminars, meetings and other PA applications. Includes USB socket for memory sticks and MP3 players etc. (not iPod)

- * High power stereo mixer amplifier
- * 4 input channels with Volume, Pan, Effect, 3 Band EQ (bass, mid & treble) and Gain controls
- * Microphone (XLR) and Line (6.35mm) inputs on each channel
- * Echo with delay, level and depth controls
- * Effect send and return
- * Stereo RCA phono inputs for CD, Tape, MP3 / iPod etc.
- * Stereo RCA phono record out sockets
- * 2-way loudspeaker enclosures with dual 6.35mm sockets
- * All 3 units have a 38mmØ top hat for tripod mounting
- * Rexine covered enclosures with metal corner protectors and rubber feet
- * Supplied with IEC mains lead

Power supply	230Vac, 50Hz
RMS output power	2 x 75w @ 4 ohms
Frequency response	20Hz - 20kHz (±3dB)
THD	<0.05% @ 1kHz
S/N ratio	>86dB
Input sensitivity - Mic	-60dBv
Input sensitivity - Line	-30dBv
Input sensitivity - Aux	-10dBv
Loudspeaker Power	60W
Loudspeaker Drivers	8" Bass and 7" X 3" Piezo Horn Tweeter
Loudspeaker Frequency Response	80Hz - 20kHz
Loudspeaker Impedance	8 ohms
Dimensions - Amplifier	400 x 285 x 225mm
Dimensions - Speaker	400 x 280 x 260mm (each)
Weight - Amplifier	10.6kg
Weight - Speaker	7.3kg (each)
Weight - total	25.2kg