



SKYTRONIC MOULDED ABS ACTIVE PA SPEAKERS

Active speaker cabinets with tough yet lightweight ABS enclosures designed for the rigors of the modern DJ. Each enclosure has a trapezoidal design with easy carry handle, and 35mmØ top hat for stand mounting.

- Lightweight ABS enclosure
- Built-in amplifier
- 2 x mic/line inputs via 6.3mm jack sockets
- Mic. volume, echo, treble, bass and master volume controls
- Low impedance compression horn driver
- Trapezoidal design
- 3 x M8 rigging points
- 35mmØ top hat with locking screw
- Supplied with stands for horizontal use
- Rigid steel grille
- Easy carry handle
- Power supply - 230Vac, 50Hz

	178.565	178.569
Woofer	30cm (12")	38cm (15")
Tweeter	25mm (1")	35mm (1.38")
Power PPMO	500W	700W
Power RMS	250W	350W
Frequency response	55Hz - 18kHz (-3dB)	50Hz - 18kHz (-3dB)
Mid/High amplifier	100w RMS	100w RMS
Frequency response	50Hz - 20kHz (-10dB)	45Hz - 20kHz (-10dB)
Low/Mid amplifier	150w RMS	250w RMS
Dimensions (L, W, D)	45.5 x 65.5 x 37 cm	52.2 x 76.5 x 47.3 cm
Crossover frequency	3kHz	3kHz
Input sensitivity	1V/p-p	1V/p-p
SPL @ 1W/1m	96dB	99dB
THD	<3%	<3%
Weight	19.5kg	26.5kg



SKYTRONIC MOULDED ABS PASSIVE PA SPEAKERS

Passive speaker cabinets with tough yet lightweight ABS enclosures designed for the rigors of the modern DJ. Each enclosure has a trapezoidal design with easy carry handle, and 35mmØ top hat for stand mounting.

- 2 x Speakon sockets
- Lightweight ABS enclosure
- Crossover fitted
- Low impedance compression horn driver
- 3 x M8 rigging points
- 35mmØ top hat with locking screw
- Trapezoidal design
- Supplied with stands for horizontal use
- Rigid steel grille
- Easy carry handle

	178.562	178.568
Woofers	30cm (12")	38cm (15")
Tweeter	25mm (1")	35mm (1.375")
Power PPMO	500W	700W
Power RMS	250W	350W
Connectors	Speakon® NL4	Speakon® NL4
Frequency response	55Hz - 18kHz (-3dB)	50Hz - 18kHz (-3dB)
Frequency response	50Hz - 20kHz (-10dB)	45Hz - 20kHz (-10dB)
Dimensions (L, W, D)	45.5 x 65.5 x 37 cm	52.2 x 76.5 x 47.3 cm
Crossover frequency	3kHz	3kHz
Dispersion	105 x 55	105 x 55
Impedance	8 ohms	8 ohms
SPL @ 1W/1m	96dB	99dB
THD	<3%	<3%
Weight	16.5kg	22.5kg