



Adastra 952.080 series of horn loudspeakers

A long established range of heavy duty, high quality circular PA horn speakers. Made from virtually indestructible ABS material offering maximum protection against shock and weather making them ideal for mounting in extreme outdoor conditions - IP rating 65. All horns are fitted with a sturdy, 270° adjustable mounting bracket and a 60cm length of double insulated connecting cable. All models are fitted with high quality aluminium voice coils, which offer high acoustical properties and reliability. 100V line models have high quality line matching transformers fitted into a sealed rear housing with wattage tapings selectable by an integral rotary switch.

	952.079	952.081	952.082	952.085	952.088
Power rms	15W	10W	15W	25W	30W
Power max	23W	15W	23W	38W	45W
Impedance	8 ohms	1k, 1.67k, 2k, 4k	670, 1k, 2k, 4k	400, 500, 670, 1k, 2k	330, 400, 500, 670, 1k, 2k
Tappings		10, 7.4, 5, 2.5, 1.25	15, 10, 5, 2.5	25, 20, 15, 5	30, 25, 20, 15, 10, 5
Freq. Response	275Hz, 7kHz	300Hz - 13kHz	275Hz - 7kHz	250Hz - 10kHz	240Hz - 10kHz (±3dB)
SPL	106dB	105dB	106dB	108dB	108dB (@ 1kHz-1W-1m)
SPL	118dB	115dB	118dB	112dB	123dB (@ 1kHz-rated-1m)
Dimensions	240 x 205mmØ	252 x 185mmØ	273 x 205mmØ	310 x 270mmØ	315 x 310mmØ
Weight	1.42kg	1.5kg	1.78kg	2.34kg	2.39kg