



adastra 2-WAY MUSIC QUALITY CEILING SPEAKER

A range of 2-way quick fit ceiling speaker with a separate bass driver and directional dome tweeter giving an excellent frequency response. White polymer frame with metal grille.

- Rotary selector switch for 100V line tapings or 8 ohms
- Specially designed locking block for fixing to ceiling tiles 1-20mm in thickness
- Spring loaded terminals for easy connection

	952.184	952.153	952.155
Dimensions:	85 x 203mmØ	100 x 227mmØ	102 x 271mmØ
Power rms:	8 Ohms - 50W	8 Ohms - 50W	8 Ohms - 60W
Power rms:	100V Line - 20W	100V Line - 20W	100V Line - 50W
Weight:	1.25kg	1.25kg	2.68kg
Frequency response:	85Hz - 20kHz	70Hz - 20kHz	60Hz - 20kHz
100v Line Tappings:	2.5, 5, 10, 15, 20W & 8 Ohms	2.5, 5, 10, 15, 20W & 8 Ohms	10, 20, 30, 40, 50 & 8 Ohms
SPL @ 1W/1m:	84dB (±2dB)	89dB (±2dB)	90dB (±2dB)
Cutout:	165mmØ	193mmØ	254mmØ
Mounting depth:	80mm	90mm	160mm