



**adastra**

Photograph is only representative

**952.794 – 40w, 952.782 – 20w and 792.788 – 15w brown outdoor 'Rock'**

Very realistic rock speakers, designed to blend into the landscape and are resistant to the elements due to the multi-layer composite cabinet which is teflon sealed and has a silicone connecting lead. The speakers are 8 ohms but can be converted to 100V line via the optional IP rated transformer (952.797)

#### 952.794 – 40w

* Low resonance cabinet		* Good bass response
* Teflon sealed		* Full range 2-way speaker system
* 20cm (8") Injection moulded polypropylene cone with Butyl rubber surround woofer		* Fixed 0.8m silicone lead
* 25mm (1") soft dome tweeter		
Power rms	40w	
Frequency response	45Hz - 19kHz	
Impedance	8 ohms	
IP rating	65	
SPL @ 1W/1m	91dB	
Dimensions	560 x 360 x 300mm	
Weight	6.8kg	

#### 952.782 – 20w

* Low resonance cabinet		* Teflon sealed
* Full range 2-way speaker system		* 13cm (5") Injection moulded polypropylene cone with Butyl rubber surround woofer
* 50mm (2") dual cone tweeter		* Fixed 0.8m silicone lead
Power rms	20W	
Frequency response	77Hz - 19kHz	
Impedance	8 ohms	
IP rating	65	
SPL @ 1W/1m	88dB	
Dimensions	280 x 255 x 210mm	
Weight	2.3kg	

#### 952.788 – 15w

* Low resonance cabinet		* Good bass response
* Teflon sealed		* Full range 2-way speaker system
* 20cm (8") Injection moulded polypropylene cone with Butyl rubber surround woofer		* Fixed 0.8m silicone lead
* 25mm (1") soft dome tweeter		
Power rms	15W	
Frequency response	45Hz - 19kHz	
Impedance	8 ohms	
IP rating	65	
SPL @ 1W/1m	91dB	
Dimensions	370 x 245 x 260mm	
Weight	4.2kg	