



## IMG Stageline MMX142 14 channel mic/line mixer

- 10 mono input channels with gain controls, 4-way equalizer with semiparametric midrange and pan pot
- 2 stereo input channels with switchable gain control (+4dB/-10dB), 2-way equalizer and balance controls
- Individual channels with control facilities
- 2 adjustable aux outputs (pre/post), PFL to all input channels
- Master insert
- Adjustable stereo aux input
- Tape record/play connections
- +48V phantom power, can be centrally switched
- Adjustable headphone output
- 482mm (19") rack installation with supplied mounting brackets

Input sensitivity	Mic, mono	0.2mV, bal.
	Line, mono	2mV, bal.
	Line, stereo	54mV, bal.
	Master insert	330mV, unbal.
	Tape	250mV, unbal.
	Aux, stereo	110mV, bal.
Outputs	Master, stereo L/R	1.23V/75Ω, bal.
	Record, stereo	300mV/600Ω, unbal.
	Master insert	330mV/1Ω, unbal.
	Aux1	3.2V/100Ω, unbal.
	Aux2	1.2V/100Ω, unbal.
	Headphones, stereo	33Ω
Frequency range	10-50,000Hz	
THD	< 0.1%	
S/N ratio	84dB, weighted	
Crosstalk	-81dB, weighted	
Equalizer	Bass	±15dB/60Hz (mono channels) ±15dB/45Hz (stereo channels)
	Midrange	±15dB/350-6,000Hz (mono channels)
	Treble	±15dB/12kHz
Phantom power	+48V	
Power supply	230V~/50Hz/25VA	
Admiss. ambient temp.	0-40 °C	
Dimensions	465x87x315mm	
Weight	5.9kg	