

Stage Line[®] MMX602 stereo 6 input mixer



6 channel microphone and line mixer

- * 6 stereo line inputs switchable to 6 balanced mono microphone inputs
- * Adjustable automatic talkover (-12dB), switchable for channel 1 or channels 1+2
- * Balance control for each stereo input channel
- * 3-way equalizer
- * 12V phantom power can be switched as required
- * LED VU meter, peak LED
- * Master output and record output
- * Output can be switched stereo/mono
- * Adjustable headphone output
- * 482mm (19") rack installation, 1u

Line input, stereo	100mV/10k Ω
Microphone input	1mV/6.6k Ω
Master output, stereo	1V/600 Ω
Record output, stereo	310mV/600 Ω
Headphones, stereo	> 8 Ω
Frequency range	20-20,000Hz
THD	0.1%
S/N ratio	62dB, unweighted
Equalizer bass	\pm 12dB/50Hz
Equalizer midrange	\pm 12dB/1kHz
Equalizer treble	\pm 12dB/10kHz
Power supply	230v AC / 50Hz / 12va
Admiss. ambient temp.	0-40 °C
Dimensions	482x47x208mm, 1RS
Weight	2.8kg
Line input, stereo	6 x RCA L/R
Microphone input	6 x XLR, bal.
Master output, stereo	1 x RCA L/R, 1 x XLR L/R, bal.
Record output, stereo	1 x RCA L/R
Headphones	1 x 6.3mm jack