

IMG Stageline MPA102, MPA202 & MPR1 mic preamps with phantom power



- 1 microphone input, XLR, bal.
- Gain, 11 steps 20-70dB
- LED green/red for operation/peak
- Phantom power +24V, can be switched on additionally
- Switchable microphone phase
- Lo cut 100Hz, hi cut 12kHz, 12dB/oct., switchable
- 1 preamplifier output
- 1 stereo line input
- 1 stereo line output
- Level control and panorama control for mixing the microphone signal to the stereo line channel

Frequency response	20-20,000Hz		
Input sensitivity	0.3-150mV switchable		
Input impedance	Mic bal.	2.2kΩ	Stereo line 10kΩ
Outputs	Line bal.	1V/100Ω -12V max.	Stereo line 1V/100Ω - 6Vmax.
Filter low cut	100Hz/-3dB, 12dB/oct.		
Filter high cut	12kHz/-3dB, 12dB/oct.		
Gain - mic	20-70dB		
Gain - stereo line	0dB		
S/N ratio, mic	> 66dB (unweighted)		
S/N ratio, line	80dB (unweighted)		
THD	< 0.01%		
Power supply	15V via supplied plug-in PSU 10VA or 4 x 9V battery		
Dimensions	116x55x125mm		

