



## PMX-120 PORTABLE PA SYSTEM - 60W + 60w RMS

The system consists of a 4 channel stereo mixer amplifier and a pair of 2-way speaker enclosures which can be fixed together to form a portable / mobile unit with integral wheels and retractable handle. Ideal for aerobic instructors, presentations, seminars, meetings and other PA applications.

- \* High power stereo mixer amplifier
- \* 4 input channels with Volume, Pan, Effect, 3 Band EQ (bass, mid & treble) and Gain controls
- \* Microphone (XLR) and Line (6.35mm) inputs on each channel
- \* Echo with delay, level and depth controls
- \* Effect send and return
- \* Stereo RCA phono inputs for CD, Tape, MP3 / Ipod etc.
- \* Stereo RCA phono record out sockets
- \* 2-way loudspeaker enclosures with dual 6.35mm sockets
- \* All 3 units have a 38mmØ top hat for tripod mounting
- \* Rexine covered enclosures with metal corner protectors and rubber feet
- \* Supplied with IEC mains lead

Power supply	230Vac, 50Hz
RMS output power	2 x 60w
Frequency response	20Hz - 20kHz (±3dB)
THD	<0.05% @ 1kHz
S/N ratio	>86dB
Input sensitivity - Mic	-60dBv
Input sensitivity - Line	-30dBv
Input sensitivity - Aux	-10dBv
Loudspeaker Power	60W
Loudspeaker Drivers	8" Bass and 7" X 3" Piezo Horn Tweeter
Loudspeaker Frequency Response	80Hz - 20kHz
Loudspeaker Impedance	8 ohms
Dimensions - Amplifier	400 x 285 x 225mm
Dimensions - Speaker	400 x 280 x 260mm (each)
Weight - Amplifier	10.6kg
Weight - Speaker	7.3kg (each)
Weight - total	25.2kg