



IMG Stageline PMX-400 200 + 200w powered mixer

- * Audio mixer and audio amplifier in a metal housing
- * 4 mono input channels with gain controls, 3-way equalizer with semi parametric midrange and pan pot
- * 4 stereo input channels with switchable gain controls (+4dB/-10dB), 2-way tone control, and balance controls
- * Adjustable effect way and monitor way, PFL to all input channels
- * Master insert L/R
- * Adjustable stereo aux input
- * Loudness push-button
- * Tape record/play connections
- * 48V phantom power, can be centrally switched
- * Adjustable headphone output
- * 2 Speakon connections
- * Protection against short circuit and overheating
- * 482mm (19") rack installation with supplied mounting brackets

Input sensitivity:

Mic 0.4mV **Line, mono** 4mV **Line, stereo** 40mV **Insert** 220mV **Tape** 140mV **Aux** 70mV

Outputs:

Master 775mV **FX** 2.5V max **Insert** 220mV **Tape (rec)** 200mV **Monitor** 200mV **Headphone** 33 Ω , stereo

Frequency response: 20-20,000Hz

THD: < 0.1%

Equalizer: **Bass** ± 15 dB/60Hz (mono channels) ± 15 dB/45Hz (stereo channels)
Midrange ± 15 dB/350-6,000Hz (mono channels)
Treble ± 15 dB/12kHz

RMS output power 4 Ω /8 Ω 2 x 200W_{RMS}/2 x 140W_{RMS}

S/N ratio 72dB

Crosstalk attenuation -69dB

Power supply 230V~/50Hz/700VA

Dimensions 350 x 325 x 145mm (w x h x d)

Weight 9.5kg